




MACHINE DE MEXICO,S.A.DE C.V.



6901ZZC3 Bearing 2D drawings and 3D CAD models

NTN 6901ZZC3 Single Row Ball Bearings

Bearing No. 6901ZZC3

| | |
|---------------------------------|---|
| Category | Single Row Ball Bearings |
| Inventory | 0.0 |
| Manufacturer Name | NTN |
| Minimum Buy Quantity | N/A |
| Weight | 0.01 |
| EAN | 4547359416541 |
| Product Group | B00308 |
| Enclosure | 2 Metal Shields |
| Precision Class | ABEC 1 ISO P0 |
| Maximum Capacity / Filling Slot | No |
| Rolling Element | Ball Bearing |
| Snap Ring | No |
| Internal Special Features | No |
| Cage Material | Steel |
| Internal Clearance | C3-Loose |
| Inch - Metric | Metric |
| Long Description | 12MM Bore; 24MM Outside Diameter; 6MM Outer Race Width; 2 Metal Shields; Ball Bearing; ABEC 1 ISO P0; No Filling Slot; No Snap Ring; No Internal Special Features; C3-Loose Internal Clearance; Steel |
| Other Features | Deep Groove |
| Category | Single Row Ball Bearing |
| UNSPSC | 31171504 |
| Harmonized Tariff Code | 8482.10.50.68 |



MACHINE DE MEXICO,S.A.DE C.V.

| Noun | Bearing |
|------------------------------|---|
| Keyword String | Ball |
| Manufacturer URL | http://www.ntnamerica.com |
| Manufacturer Item Number | 6901ZZC3 |
| Weight / LBS | 0.024 |
| Outer Race Width | 0.236 Inch 6 Millimeter |
| Inner Race Width | 0 Inch 0 Millimeter |
| D | 0.945 Inch 24 Millimeter |
| d | 0.472 Inch 12 Millimeter |
| bore diameter: | 12 mm |
| static load capacity: | 1460 N |
| outside diameter: | 24 mm |
| precision rating: | ISO Class 0 |
| overall width: | 6 mm |
| finish/coating: | Uncoated |
| bore type: | Round |
| bearing material: | High Carbon Chrome Steel |
| closure type: | Double Shielded |
| cage material: | Steel |
| row type & fill slot: | Single Row Non-Fill Slot |
| inner ring width: | 6 mm |
| snap ring included: | Without Snap Ring |
| outer ring width: | 6 mm |
| internal clearance: | C3 |
| maximum rpm (grease): | 27000 rpm |
| operating temperature range: | -40 to 120 ° C |
| fillet radius: | 0.3 mm |
| dynamic load capacity: | 2890 N |
| manufacturer product page: | Click here |